



شركة كويك ميكس
مركز الإضافات الأسمنتية
الناعمة و مواد البناء عالية التكنولوجيا

Quick T.F

Product description:

Quick T.F is a cement-additive that is used with the cement mortar as an admixture to increase cohesion with back surface.

Quick T.F is one of the most advanced and strongest cement-additive for tough repairing mortar available in the market today, that is because of the great chemical composition which includes great components. These components react efficiently with cement to completely prevent hair cracks and give the ultimate in bonding and cohesion with back surface

Scope of use:

Quick T.F is an excellent choice for:

- Interior or exterior thick plaster works
- Tough Restoration and repairing works
- Tile fix mortar

Advantages:

- **Quick T.F** is a must additive in repairing works
- **Quick T.F** is the right choice as a cement additives for both hand-applied or machine-applied thick plastering
- **Quick T.F** gives user both Excellent cohesion with back surface and the ability to apply very thick plaster layers
- **Quick T.F** decrease absorption levels of water and humidity so it's perfect in coastal works
- **Quick T.F** is one of the best Time, cost saving solutions available.
- **Quick T.F** gives perfect tile fix mortar

Technical specifications:

Product Form	powder
Product Color	Light gray
Standards	ASTM C- 494 TYPE – C
Dose	1-2 packet(s) Quick T.F/50 kg cement / 150 kg sand
Water/Quick T.F ratio	Less than normal amount by 10% - 15%
Coverage Rate	According to previous dose 20 m ² [in case of 1 cm thickness of mortar]
Package	Cartoon box contains 24 packets each packet 150 g
Shelf-life	1 year

Applying As a repairing mortar:

Add **1-2** packet(s) **Quick T.F** to **50** kg of cement to **150** kg of sand and add water less than usual by 10% - 15% then mix well (Mechanically mixing is recommended)

Applying as A tile Fix

Add **2** packets **Quick T.F** to **50** kg of cement and add clear water (**10 -12**) liters then mix well (Mechanically mixing is recommended)

Important notes

- **Quick T.F** packet should be used once at a time and not divided
- **Quick T.F** dose not require the use of any other additives
- **Increasing** the dose of **Quick T.F** dose not affect mortar properties it just prolongs hardening time

Egypt: CAC , Cement Additives Center. Alexandria, 18 Saleh Ali St., Tel and Fax +203 5775 909

Email: Cac@tasniem.com Mob: 0100 12628 96 - 0106 410 48 76 GPS: 31.2429071N, 29.9716768E

KSA Soltana st., Gamgoom bldg. Al-Madina Almonwwara KSA Tel & fax +966 4838 90 40 cell phone: 966 5657 84000
U.A.E Al Yosr For Trading and Development RAK FTZ U.A.E Tel & fax 07 227 1653 - cell phone:+971 5043 12 495